

## KFI-40

高精度光纤识别仪



### 产品特性和功能

- 适用于0.25/0.9/2.0/3.0mm光纤，方便快捷，简单易操作。
- 三种常用识别测试音调。
- 体积小巧，携带方便，使用时无需单独更换夹具。
- 识别光纤光源传播方向，声音警报提醒。
- LED背光显示，适用各种环境，无需辅助照明。
- 测试灵敏度  $-40 \text{ dBm}$  to  $10 \text{ dBm}$ 。
- 电池低电量智能提醒。

多合一夹具



裸纤



0.9mm 尾纤



皮线



3.0mm 跳线

产品规格参数:

型号	KFI-40
波长识别范围	800nm to 1700nm
信号识别类型	CW,270 Hz $\pm$ 5%,1 kHz $\pm$ 5%,2 kHz $\pm$ 5%
探测器类型	$\phi$ 1mm InGaAs 2 pcs
适配光纤类型	通用 $\phi$ 0.25(裸纤), $\phi$ 0.9, $\phi$ 2.0, $\phi$ 3.0 光纤皮线
信号方向	LED指示灯左右方向指示
光功率读数范围	-40 dBm to 10 dBm
信号频率范围	270Hz,1kHz,2kHz
电源类型	AA*2
工作温度范围	-10°C to 60°C
储存温度范围	-25°C to 70°C
产品尺寸	195mm*10mm*8mm
产品质量	235g

## 产品清单:



## 联系我们:

江苏吉星光通讯科技有限公司

## 总公司:

地址: 江苏省南京市雨花区宁双路十八号沁恒科技园

电话: 025-66047688

网址: [www.jxgtx.com](http://www.jxgtx.com)

邮箱: [ventas@komshine.com](mailto:ventas@komshine.com)

- \* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.
- \* Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.
- \* This catalogue is printed using environmentally friendly paper and ink.