


KLS-35

稳定光源




产品特性

- 2.5mm通用接口+SC适配器
- 输出功率-5dB
- 单模波长1310nm/1550nm
- 多模波长850nm/1300nm
- 单多模波长850nm/1300nm/1310nm/1550nm
- PON波长1310nm/1490nm/1550nm
- 硅胶机壳保护设计，防坠落2m
- LED背光功能，不惧黑暗



背光显示



一键启动



自动关机



即插即用



超长待机



硅胶保护壳

产品特点



防摔



小巧



支架设计



分体保护套

KLS-35



接口附件



SC



FC



ST

波长 (nm)	1310+1550nm (KLS-35-S)
	850+1300nm (KLS-35-M)
	850+1300+1310+1550nm (KLS-35-MS)
	1310+1490+1550nm (KLS-35-PON)
输出功率	-5dB
光连接器	SC+2.5mm通用 (1.25毫米LC可选)
电源	碱性电池(3 AA 1.5V 电池)
输出稳定性	±0.05dB/15mins; ±0.1dB/ 8小时
调制频率	CW,270Hz,1KHz,2KHz
体积/重量	160x85x45mm / 220g

产品展示



总公司

江苏吉星光通讯科技有限公司

联系我们

地址：江苏省南京市雨花区宁双路十八号沁恒科技园

电话：025-66047688

网址：www.jxgtx.com

邮箱：ventas@komshine.com

* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.

* Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.

* This catalogue is printed using environmentally friendly paper and ink.