


# KPM-25V

迷你式光功红光一体机




## 产品特性


- 2.5mm通用接口
- 波长850~1625nm
- 可手动校准数值
- 防摔硅胶套，保护机器
- ±0.2dB精确度
- 测量范围-70~+6dBm/-50~+26dBm
- 拥有独立的VFL功能
- LED背光功能



背光显示



一键启动



自动关机



分辨率0.01dB



7波段检测



硅胶保护壳

# 7波长可选

850nm

980nm

1300nm

1310nm

1490nm

1550nm

1625nm



# 拥有独立的 VFL功能

## 测试断线方便快捷



### 产品特点



防摔



小巧



分体保护套



LED灯



# KPM-25V



FC



SC



LC(选配)



ST

光功率计部分	
型号	KPM-25V
波长范围 (nm)	800~1700
探头类型	InGaAs
功率测量范围 (dBm)	-70~+ 6 dBm / -50~+26dBm
不确定度	±5%
光纤类型	SM MM
标准波长 (nm)	850、980、1300、1310、1490、1550、1625
连接器	2.5mm通用适配器
显示分辨率	线性显示0.1% 对数显示: 0.01dBm
红光源部分	
工作波长	650nm±10nm
光源	FP-LD激光器
输出功率	1mW、10mW、20mW
连接器	2.5mm通用适配器
工作模式	CW连续光或调制光
调制频率	2Hz
工作温度 (°C)	-20~+75
存储温度 (°C)	-40~+85
自动关机时间 (min)	10
电池持续工作 (h)	100小时 (背光关闭状态)
电源	3节5号电池
重量	300g

## 产品展示



### 总公司

江苏吉星光通讯科技有限公司

### 联系我们

地址：江苏省南京市雨花区宁双路十八号沁恒科技园

电话：025-66047688

网址：[www.KomShine.com](http://www.KomShine.com)

邮箱：[info@komshine.com](mailto:info@komshine.com)

\* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.

\* Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.

\* This catalogue is printed using environmentally friendly paper and ink.