

KPM-25m & KLS-25m

小型功率计及光源



产品特性

- 高灵敏度，大动态范围。
- 通用接口设计：FC/SC/ST/LC接口。
- 标配FC,LC,SC,适配接口。
- 迷你型机壳保护设计，小巧大方。
- 快速响应，无需预热。
- 低电压功能显示。
- 自动关机，自动关闭背光功能可选。
- 对数功率（dBm）和线性功率（xW）指标测量。



背光显示



一键启动



自动关机



即插即用



超长待机



硅胶保护壳

产品特点



防摔



小巧



支架设计



分体保护套

KPM-25M



接口附件



SC



FC



ST

波长 (nm)	800~1700nm
测量范围	-70+3dBm / -50~+26dBm
光连接器	FC+SC+2.5mm通用 (1.25毫米LC可选)
电源	碱性电池(2 AAA 1.5V 电池) (需自行购买)
显示单元	dB / dBm / w
分辨率 (dB)	0.01
体积 / 重量	130x65x35mm / 180g

KLS-25M



接口附件

SC

FC

ST

波长 (nm)	850+1300nm / 1310+1550nm
输出功率	-5dB
光连接器	FC+SC+2.5mm通用 (1.25毫米LC可选)
电源	碱性电池(2 AAA 1.5V 电池) (需自行购买)
输出稳定性	±0.05dB/15mins; ±0.1dB/ 8小时
调制频率	CW,270Hz,1KHz,2KHz
体积 / 重量	130x65x35mm / 180g

Packaging display:



Contact Us:

江苏吉星光通讯科技有限公司

Head Office:

地址: 江苏省南京市雨花区宁双路十八号沁恒科技园

电话: + 86 25 8687 1288

传真: + 86 25 8687 1288

网址: www.komshine.com

邮箱: sales@komshine.com

* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.*

Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.

* This catalogue is printed using environmentally friendly paper and ink.