


KPM-35 & KLS-35

小型光功率计及光源



产品特性

- 高灵敏度，大动态范围。
- 通用接口设计：FC/SC/ST/LC接口。
- 标配FC,LC,SC,适配接口。
- 迷你型机壳保护设计，小巧大方。
- 快速响应，无需预热。
- 低电压功能显示。
- 自动关机，自动关闭背光功能可选。
- 对数功率（dBm）和线性功率（xW）指标测量。



背光显示



一键启动



自动关机



即插即用



6波长检测



硅胶保护壳

产品特点



防摔



小巧



支架设计



分体保护套

KPM-35



Interface accessories



SC



FC



ST

波长(nm)	800~1700nm
测量范围	-70+3dBm / -50~+26dBm
光连接器	FC+SC+ 2.5mm 通用 (1.25mm LC可选)
电源	碱性电池(3 AA 1.5V 电池) (需自行购买)
显示单元	dB / dBm / w
分辨率 (dB)	0.01
体积/重量	160x85x45mm / 220 g

KLS-35



Interface
accessories



SC



FC



ST

波长(nm)	SM 1310/1550nm (KLS-35S)
	MM 850/1300/1310/1550nm (KLS-35MS)
	PON 1310/1490/1550nm (KLS-35P)
输出功率	-5dB
光连接器	FC+SC+ 2.5mm 通用 (1.25mm LC可选)
电源	碱性电池(3 AA 1.5V 电池) (需自行购买)
输出稳定性	±0.05dB/15mins; ±0.1dB/ 8hours
调制频率	CW,270Hz,1KHz,2KHz
体积/重量	160x85x45mm / 220g

PACKAGING DISPLAY:



CONTACT US:

江苏吉星光通讯科技有限公司

HEAD OFFICE:

地址：江苏省南京市雨花区宁双路十八号沁恒科技园

电话: + 86 25 8687 1288

传真: + 86 25 8687 1288

网址: www.komshine.com

邮箱: sales@komshine.com

* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.
 * Company and product names appearing in this catalogue are resisterd marks or trademarks of respective companies.
 * This catalogue is printed using environmentally friendly paper and ink.